

BluSeal Tunnel Liner ground water infiltration management

BluSeal Tunnel Liner WATER INFILTRATION MANAGEMENT







BluSeal Tunnel Liner PRODUCT INFORMATION

Bluey are leading Australian tunnel waterproofing specialists with proven experience on leading infrastructure projects

WHERE DO WE USE BLUSEAL TUNNEL LINER?

Blu**Sea**l Tunnel Liner is chosen where there is a need for 'dryness' or management of groundwater infiltration in a tunnel.

Blu**Sea**l Tunnel Liner provides the highest surety of durability, environmental management and aesthetic outcomes required on a modern day construction project

WHY BLUSEAL TUNNEL LINER?

Water infiltration control

Understand and manage the risks associated with ground water in an underground environment.

Proven large scale application and project management of major infrastructure projects







SHEET MEMBRANE TUNNEL LINING PROJECTS

Epping to Chatswood Rail Link, Sydney

Eastlink Project, Melbourne

Northern Gateway Project, Auckland (New Zealand)

City West Cable Tunnel, Sydney

NSBT Gibbon Street Shaft, Brisbane

Boggo Road Tunnel, Brisbane

Airport Link Project, Brisbane

Electrified Double Track Tunnel, Berapit (Malaysia)

SPRAY APPLIED LINING AND TUNNEL INJECTION SEALING PROJECTS

Cross City Tunnel, Sydney

North Kiama Bypass, NSW

M5 East Tunnel Sealing, Sydney

Eastern Distributor Tunnel Sealing, Sydney

M2 Tunnel Widening, Sydney

Blu**Seal** Tunnel Liner

EXPERIENCE

Bluey's four key offerings in major tunnel infrastructure projects, with proven experience and successful results



PROJECT MANAGEMENT ACTIVITIES

Selection and procurement of specialist membrane welding & testing equipment

Training and supervision of local installers to meet the demand of numerous concurrent waterproofing work fronts

Materials handling and delivery from abroad

Quality control of both material supply and site installation

General site management of the installation works

TRAINING

Bluey's Engineers specialise in onsite techniques to ensure that the Client, its designers and applicators receive full support during the entire material selection, installation and testing process. Bluey is able to offer training and quality inspections on site either directly or through third party trained specialists accredited by Bluey. For all of our products we are also able to recommend competent applicators who have experience in applying our range of products.

PRODUCT SUPPLY

When Bluey is engaged for work on your project, you can be sure that you will have access to the best value products around the World.

Due to our ongoing work on large projects in the region, we have a broad understanding of the most efficient manufacturers of each product depending upon the size, location and technical details of your underground structure.

Bluey will work through the design process and ensure that the right product is selected to give the best outcome. Consideration will be given to the local environment, tunnel methodology, installation techniques, and performance criteria. Bluey will also take care of some of the more complex logistical issues such as selection of membrane roll lengths to reduce wastage, roll widths, container packing methods and delivery schedules to keep ahead of construction activities.

SITE SUPPORT

Onsite, Bluey uses its experience in tunnel lining to ensure that waterproofing and drainage works are well managed so that you can get on with the more important task of building the tunnel.

We ensure that the design of gantries and membrane details are developed to ensure installation can keep ahead of concrete lining. Our role onsite extends beyond project management of membrane lining, for example, we will work together with shotcreting crews to ensure the quality is acceptable for membrane placement. Our experience will keep all parties satisfied that activities are being coordinated to ensure a good outcome for the Client.

Most importantly of all, we will develop systems of safe work in the tunnel environment to ensure that the waterproofing and drainage systems are installed without harm to others. We will take care of the procedures for handling and storage of plastic materials within the tunnel environment to significantly reduce manual handling requirements and also eliminate fire safety issues. Our experience in this field will prove to be a valued asset.

It is our job to plan every aspect of tunnel and drainage installation in your underground environment. Our Project Managers will guide you through the entire project to ensure that all aspects of the installation are considered and well planned for.



BluSeal Tunnel Liner SYSTEM SELECTION

WATERPROOF LINING SYSTEMS

Tunnel sealing and drainage systems typically fall into the following categories:

Drainage Layer Linings

Spray-on Liquid Membrane Linings

Sheet Membrane Linings

ASSESSMENT

These systems have varying application benefits and limitations

The system will generally be designed around final tunnel requirements for 'dryness'

Within the framework of other considerations:


- Site Conditions
- Economic Implications
- Concrete Lining Methodologies and Program
- International Standards

SITE CONDITIONS

Ingress of water at the time of excavation and membrane application

Substrate preparations planned to be carried out

Underground access constraints







ECONOMIC IMPLICATIONS

Budget available

Constructors risk perception depending on previous experience (fix it later)

Not a budget priority to the contractor

CONCRETE LINING METHODOLOGIES AND PROGRAM

Insitu concrete

Shotcrete permanent lining systems

Planned sequencing of the works

INTERNATIONAL STANDARDS

Specification for tunnelling, British Tunnelling Society and The Institution of Civil Engineers, 3rd Edition 2010

DVS 2225 – Joining of Lining Membrane Made of Polymer Materials in Geotechnical and Hydraulic Engineering

International Association of Geosynthetic Installers – HDPE and LLDPE Geomembrane Installation Specifications

DS 853 - Deutsche Bahn AG - German Railway Standards

BluSeal Tunnel Liner SURFACE PREPARATION

SURFACE PREPARATION

INSPECTION & ACCEPTANCE OF SHOTCRETE / SUBSTRATE SMOOTHNESS

Maximum aggregate size 4 to 10mm (depending on system)

Irregularities shall not exceed 200mm on any Im curved edge

Cover or remove protruding objects such as rockbolts

Seal or divert running water

Maintain drainage prior to concrete pour

DRAINAGE LAYERS

DRAINAGE LAYER LININGS

Technically not a 'watertight' liner Provides an annulus drainage path

Alleviates the build up of external hydrostatic pressures on the structure

Typically used for tunnels constructed in good quality rock


DRAINAGE LAYERS

DRAINAGE MEDIUMS













Blu**Seal** Tunnel Liner SURFACE MEMBRANE

SPRAY APPLIED MEMBRANE

SPRAY-ON LIQUID MEMBRANE LININGS

Developed out of their similar use within the mining industry

Have only been used on a limited basis world-wide for waterproof of tunnels

Materials include: acrylics / bitumen / cement latex / polyurethane / polyurea

SPRAY MEMBRANE USES

Remediation of rock-face weathering

Management of minor water infiltrations

Waterproofing membrane in specific cases

SPRAY-ON LIQUID MEMBRANE LININGS

Membrane can not be applied to damp or wet shotcrete surfaces

Consistent quality difficult to achieve in tunnel environment

Less durable than PVC or VLDPE sheet membranes

Generally not suitable for use in tanked tunnels





Blu**Seal** Tunnel Liner

SHEET LININGS

SHEET MEMBRANE LININGS

Most robust and watertight protection for a tunnel structural lining

Impermeable water barrier between concrete lining and surrounding strata

Internationally recognised as the most reliable method of tunnel waterproofing

Used as either:

- 'Umbrella', shedding water from the tunnel 'crown' down into an invert drainage.
- Fully 'encapsulated' or 'tanked' structural lining, which limits water ingress.

VARIATIONS IN SHEET MEMBRANE SYSTEMS

Material type and thickness

Drainage and protection layers

Welding and fixing methods

Secondary protection provisions

External compartmentalisation systems to maintain water tables

INSTALLATION OF GEOTEXTILE FLEECE

Installed as membrane protection or drainage

Generally non-woven 100% polypropylene

Minimum weight of 700 g/m²

Flammability class B2







INSTALLATION OF ROUNDELS (MEMBRANE FIXING DISCS)

Nail fixed through the geotextile fleece

Compatible for hot air (spot) welding to the sheet membrane

Fixed on an average of 1 per m² for walls and 2-3 per m² for crowns

Rock substrate Shotcrete support and smoothing layer 2mm PVC membrane (fixed to rondels by hand hot air welding and to adjacent membrane sheets by 100mm lap and double wedge welding) Geotextile fleece (installed against smoothing shotcrete by nail fixing) Rondels fixed by nail on geotextile through to shotcrete (temporary holding membrane in location until permanent lining concrete installation)

INSTALLATION AND WELDING OF MEMBRANE SHEET WATERPROOFING

Drained tunnels shall generally be 2mm thick

PVC-P or VLDPE

The membrane shall have a 'signal' layer

Flammability class shall be appropriate for the site

Heat weld to previously installed roundel fixings

Install with sufficient slack to avoid potential overstressing

Install 'snug enough' to avoid folds developing during concrete placement

All seams are pressure tested



PORTALS AND CROSS PASSAGES

Three way curvature Heavy reinforcement

TBM CROSS PASSAGES

Connection to precast segments














■ 10 Bluey Technologies



INSTALLATION ACCESS EQUIPMENT

Fixed gantry, mobile or automated gantry







TERMINATIONS

Pressure terminations

Epoxy tape terminations

PENETRATIONS

Through fixings (condom bolts)

Drainage and grouting







WATERSTOPS

Compartmentalisation Longitudinal and Radial



■ 12 Bluey Technologies



BluSeal Tunnel Liner CASE HISTORIES

BRISBANE AIRPORT LINK PROJECT

Twin 5.1km tunnels connecting Brisbane city with the northern suburbs and airport precinct.

PROJECT DETAILS

Drained tunnel

TBM bored

Cast insitu concrete lining

I litre/s/100m tunnel length inflow

No damp patches

SOLUTION

Bluey designed unique dimple sheet fixings

Materials selected to allow double seam welding and testing

Manufactured in Norway to Bluey specification

Bluey partnered German Installer Naue

Project complete with no damp patches

FEATURES

Drained and tanked tunnel profiles with associated groundwater drainage systems and external compartments between profiles

System compatibility for both insitu concrete and shotcrete permanently lined tunnels

Tanked connections between mined and TBM tunnels

BENEFITS

Tunnel functionality for high speed tollway traffic flows with no 'drips' from above or visible damp patches from below

Groundwater impacts minimised with tunnel inflows controlled and handled by the designed drainage and pumping systems







BluSeal Tunnel Liner CASE HISTORIES

MELBOURNE EASTLINK PROJECT

Twin 1.6km tunnels under the environmentally sensitive community parkland area of Mullum Mullum Creek

PROJECT DETAILS

Fully tanked tunnel lining

40m water head

13 cross passages

SOLUTION

International Standard waterproofing design conformance

2mm and 3mm membrane double seam welding

Radial waterstop at every block joint

Bluey DVS qualified supervision

Every membrane seam pressure tested and verified

FEATURES

150,000 square metres of 2mm LLDPE sheet membrane to both the invert and obvert (arch) of the tunnels

Waterstop joint protection and lining compartmentalisation

External lining z-profile compartments

Post completion injection systems

BENEFITS

Minimal long term environmental impact on the surrounding water tables with nil effects on the Mullum Mullum creek water levels above

Negligible water inflows that needed to be handled by operational drainage pumping systems for the life of the tunnels







I 14 Bluey Technologies



BluSeal Tunnel Liner CASE HISTORIES

EPPING TO CHATSWOOD RAIL LINK

12KM TWIN TUNNELS 7M DIAMETER

PROJECT DETAILS: SOLUTION:

Drained tunnel Bluey designed unique dimple sheet fixings

TBM bored Materials selected to allow double seam

Cast in-situ concrete lining welding and testing

I litre/s/100m tunnel length inflow

Manufactured in Norway to Bluey

No damp patches specification

Bluey partnered German Installer Naue

Project complete with no damp patches



AUCKLAND NORTHERN GATEWAY PROJECT

300M TWIN TUNNELS DUAL CARRIAGEWAY ROAD TUNNEL

PROJECT DETAILS: SOLUTION:

Drained tunnel lining International Standard waterproofing design

Environmentally sensitive conformance

Cross passages 2mm and membrane double seam welding

Road header excavation Radial waterstop every 50m


Cast in-situ concrete lining

Bluey DVS qualified supervision

Client supplied labour for installation

Every membrane seam pressure tested

and verified



SYDNEY CITY WEST CABLE TUNNEL PROJECT

SHAFT, BACK DRIVE AND CAVERNS

PROJECT DETAILS: SOLUTION:

Fully tanked lining International Standard waterproofing

design conformance

Aggressive ground water

Sensitive electrical equipment 2mm and membrane double seam welding

Road header and hand excavation Radial waterstop at every construction joint

Cast in-situ concrete lining Bluey DVS qualified supervision

Subcontractor labour for installation

Every membrane seam pressure tested

and verified



BluSeal Tunnel Liner PRODUCT SUMMARY

SUMMARY

Australia is an international leader in tunnel waterproofing applications.

Work standards have improved significantly in recent years through training and partnering programs.

Contractors are saving time and money by engaging the right methods, equipment and people at the early phases of project planning.

There is now a rapidly growing list of successfully sealed tunnels completed in Australia in terms of cost, program and final outcome for water infiltration.

We are striving to improve this record by working together with industry, learning from our experiences and continuing to engage international expertise.





BluSeal Tunnel Liner PRODUCT SUMMARY



Bluey Technologies PRODUCT RANGE

blu**Cem**

Blu**Cem** API0

Blu**Cem** RF20

Blu**Cem** FC

Blu**Cem** HB range

Blu**Cem** HEI0

Blu**Cem** HE80

Blu**Cem** HE80AG

Blu**Cem** HE80HT

BluCem HS100 range

BluCem HS200 range

Blu**Cem** EA02

Blu**Cem** GP60

Blu**Cem** UF40

Blu**Cem** UW range

blu**Geo**

Blu**Geo** Powerthread range Blu**Geo** SD Anchors range Blu**Geo** ST Rock Bolts range Blu**Geo** Swellex range Blu**Geo** Tekflex

blu**Rez**

BluRez Crackseal III
BluRez Crack Seal I50
BluRez Crackseal NV
BluRez Carbostop
BluRez Carbostop 42D
BluRez Epoxy 225
BluRez Epoxy 480
BluRez Epoxy 480UT

Blu**Rez** Epoxy 575 CG


Blu**Rez** Epoxy 655

blu**Seal**

BluSeal Anchor Knob Sheet BluSeal Britdex Membrane BluSeal Moulding Putty BluSeal Dust Control 10 BluSeal Road Sealer 10 BluSeal Containment Liner BluSeal PVC Tunnel Liner BluSeal Injection Kit









Bluey Technologies CONTACT

BRISBANE

Bluey Technologies Pty Ltd Suite 6, Level I 531 Sandgate Road Clayfield QLD 4011 Australia

+61 7 3135 9440

SYDNEY

Bluey Technologies Pty Ltd Unit 3, 35 Higginbotham Road Gladesville NSW 2111 Australia

+61 2 9114 9445

MELBOURNE

Bluey Technologies Pty Ltd Unit D9, Hallmarc Business Park 2A Westall Road Clayton VIC 3168 Australia

+61 3 9017 4942

KUALA LUMPUR

Bluey Technologies Sdn Bhd 8A, I-4 Prima Damansara Jln Chempenai Bukit Damansara 50480 Kuala Lumpur Malaysia +60 1734 97374

+65 8455 1291

SINGAPORE

Bluey Technologies Pte Ltd 27 Foch Road 02-06 Hoa Nam Building Singapore 209264





STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the informatio herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.

NOTE:

Field service where provided, does not constitute supervisory responsibility. Suggestions made by Bluey Technologies Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Bluey Technologies Pty Ltd are responsible for carrying out procedures appropriate to a specific application.

© Bluey Technologies Pty Ltd

Bluey Technologies Pty Ltd

Australia & Asia-Pacific bluey@bluey.com.au www.bluey.com.au