

BluSeal VLDPE Roundel

VLDPE Membrane Fixing Disc

Material Description

BluSeal VLDPE Roundel is a fixing element for the lining and anchorage of VLDPE membrane in tunnel waterproofing.



BluSeal VLDPE Roundel is used to fix geotextiles and waterproofing membranes in tunnel and underground environments.

Product Data

Packaging	600 pieces per box
Appearance (colour)	Black

Characteristics and Benefits

- Excellent weldability
- Flexibility at low temperature
- High resistance to impact
- Compatible with **BluSeal VLDPE Tunnel Liner**
- Placing on the concrete or substrate by a pressure gun with a nail and washer



BluSeal PVC Roundel

PVC Membrane Fixing Disc

Performance Data

Tested Characteristic	Standard	Result
Weight Density	ISO 1183	0.92g/cm ³
Elongation	ISO 527	500% @ break

Disclaimer

BluSeal VLDPE Roundel-ANZ-V1-102025

This Technical Data Sheet is provided for general information and instruction only. The properties and characteristics set out herein represent typical testing results under laboratory conditions. Results of actual product characteristics may vary slightly. Site-specific and project-specific conditions may affect product performance, including without limitation: surfaces, environmental conditions, contact conditions, storage conditions, storage timeframes, weather, and climatic or seasonal conditions. Not all product parameters are batch tested as part of the manufacturing quality control process, and performance may vary between batches.

If Bluey gives any express written product warranty in relation to the product, that warranty is subject to the foregoing qualifications, despite anything to the contrary in any other document. All other representations, advice, suggestions or promises regarding the product's performance or its implementation, whether verbal or in writing, and whenever given, including in the course of any field services, are expressly disclaimed. Without limiting the foregoing, Bluey will have no liability for loss or damage of any kind if any application specifications are not followed.

The foregoing is not intended to exclude any warranties or guarantees which by law cannot be excluded. Subject only to the foregoing provisions of this Notice, and to the extent permitted by law, Bluey disclaims all liability for loss or damage of any kind suffered as a result of or in connection with the product or its implementation. If such liability cannot be wholly excluded, Bluey's liability will, to the extent permitted by law, be limited to the replacement of the product itself or the direct cost of replacement of the product itself (not including any collateral or consequential loss or damage of any kind).

Bluey Technologies Pty Ltd

ABN 36 115 613 646
Suite 102, 2 Burbank Place
Norwest NSW 2153

Freecall: 1300 227 300
www.bluey.com.au

Emergency Advice

1300 954 583 within Australia (24hr)