

BluSeal AD50

Silane-modified Polymer Adhesive

Material Description

BluSeal AD50 is a single component thixotropic paste which requires only careful application to form a high bond construction adhesive. **BluSeal AD50** is a hand cartridge applied, safe and odourless adhesive suitable for civil engineering applications. **BluSeal AD50** incorporates silane modified polymers which are durable, tolerant to extreme temperature variations and ultra-high bonding to many surfaces. **BluSeal AD50** is a silane-modified polymer which cures when exposed to the atmosphere to form a flexible, easy to apply, single component, high bond compound. **BluSeal AD50** is designed to be used as a stand-alone joint sealant or otherwise in conjunction with **BluSeal JS50**. Combination with **BluSeal JS50** will create an ultra-high movement capable joint seal for fixing between concrete elements where large differential deflections are expected.

Due to its excellent bonding capabilities, even in damp environments, **BluSeal AD50** is particularly suitable for underground civil engineering applications.

Characteristics and Benefits

- Suitable for bonding to moist surfaces, even underwater
- Solvent and silicone free
- Odourless
- No isocyanates and plasticiser based on phthalate
- Low shrinkage
- Durable
- Extreme temperature variation tolerant
- Ultra-high bonding
- Adheres to a wide range of substrates

Areas of Application

- Structural adhesion
- Movement joint sealing
- Architectural fixing
- Damp area adhesion
- TBM gasket adhesion
- Road reflectors (Cats eyes)

Product Data

Material Basis	SMP
Consistency	Pasty
Colour	Black, grey

Application Specification

Concrete Preparation

1. All defective host substrate must be removed prior to application. Defective material includes cracked or structurally weakened surfaces and also chloride contaminated and carbonated concrete. The surfaces shall not contain substances containing tar, as otherwise the adhesion is reduced. The application on fresh bitumen is not recommended for the same reasons. On old bitumen an adhesion can be reached of maximum 0.45 N/mm², as long as the surface is free of grease. A concrete corrosion expert must be consulted for critical projects or structural applications.
2. Host concrete must be roughened and aggregate exposed to ensure good bond. High pressure water blasting or mechanical chipping of the surface is recommended for this purpose.
3. All surfaces must be free of dust, oils and surface contaminants. This may require steam cleaning or high pressure water blasting if site conditions permit.

Priming

1. For permeable surfaces and to achieve higher bond in general, please contact Bluey for a range of suitable primers.

Placement

1. Placement of **BluSeal AD50** can be completed using hand cartridges.

BluSeal AD50

Silane-modified Polymer Adhesive

Application

- After suitable joint and substrate preparation, **BluSeal AD50** is gunned or trowelled into place. Application areas must be properly formed ready for final placement. The recommended forming material is polyethylene tape.

Curing

- BluSeal AD50** cures by reaction with atmospheric moisture. The reaction starts at the surface and progresses towards the centre of the cross section. The curing speed depends on the relative humidity and the temperature. At low temperatures the water content of the air is lower and the curing reaction proceeds more slowly.

Product Specification Clause

SILANE-MODIFIED POLYMER ADHESIVE - The high bond adhesive used for this project shall be a one component thixotropic paste which requires only careful application to form a durable high bond product. It shall be pre-packaged and tested to achieve the technical requirements outlined in the technical data table detailed below in accordance with the standards shown. BluSeal AD50 manufactured by Bluey Technologies or similarly performing products may be accepted for use on this project.

Performance Data

Description	Standard	Requirement HDPE
Specific Density	DIN EN ISO2811-1	1.5g/cm ³ @ 23°C
Dynamic Viscosity	DIN EN ISO2555	2000Pas @ 23°C
Tack-Free Time	ASTM C679	15 min @ 23°C
Setting Process		3mm @ 24 hours @ 23°C
Tensile Strength	DIN EN ISO 527	1.3N/mm ²
Elongation at Break	DIN EN ISO 527	350%
Shore A Hardness	DIN ISO7619-1	40
Temperature Resistance		-30°C to +80°C
Bond Strength at Concrete	DIN EN 1542	1.65N/mm ² Dry 1.65N/mm ² Slightly moist

BluSeal AD50

Silane-modified Polymer Adhesive

Disclaimer

BluSeal AD50-ANZ-V1-112025

This Technical Data Sheet is provided for general information and instruction only. The properties and characteristics set out herein represent typical testing results under laboratory conditions. Results of actual product characteristics may vary slightly. Site-specific and project-specific conditions may affect product performance, including without limitation: surfaces, environmental conditions, contact conditions, storage conditions, storage timeframes, weather, and climatic or seasonal conditions. Not all product parameters are batch tested as part of the manufacturing quality control process, and performance may vary between batches.

If Bluey gives any express written product warranty in relation to the product, that warranty is subject to the foregoing qualifications, despite anything to the contrary in any other document. All other representations, advice, suggestions or promises regarding the product's performance or its implementation, whether verbal or in writing, and whenever given, including in the course of any field services, are expressly disclaimed. Without limiting the foregoing, Bluey will have no liability for loss or damage of any kind if any application specifications are not followed.

The foregoing is not intended to exclude any warranties or guarantees which by law cannot be excluded. Subject only to the foregoing provisions of this Notice, and to the extent permitted by law, Bluey disclaims all liability for loss or damage of any kind suffered as a result of or in connection with the product or its implementation. If such liability cannot be wholly excluded, Bluey's liability will, to the extent permitted by law, be limited to the replacement of the product itself or the direct cost of replacement of the product itself (not including any collateral or consequential loss or damage of any kind).

Bluey Technologies Pty Ltd

ABN 36 115 613 646
Suite 102, 2 Burbank Place
Norwest NSW 2153

Freecall: 1300 227 300
www.bluey.com.au

Emergency Advice

1300 954 583 within Australia (24hr)