

# BluRez CSI50

## HYDROPHILIC POLYURETHANE INJECTION RESIN

BluRez CSI50 is a single component polyurethane which reacts with water to form a hydrophilic flexible seal.

BluRez CSI50 is designed for the sealing/grouting and elastic connection of fissures and cavities in buildings and other civil engineering structures constructed of concrete, brickwork and natural stone. Application uses such as tunnel linings, concrete foundations, subterranean curtains, retaining walls, slab on ground and bridge abutments. Generally, the BluRez CSI50 is most suitable for use in consistently damp or wet environments.

### Advantages

- Potable water use approved in accordance with AS/NZ 4020:2005
- Hydrophilic for high water stopping properties
- Easy to use, single pack
- Highly flexible for live structures
- Compatibility with most surfaces
- Rapid foam and gel times

### Preparation

Evaluate joint or crack for injection. Drill holes either side of the crack, sloping towards the crack at an angle of approximately 45°, beginning at a distance of 120 - 150 mm from the crack. Insert packer at a depth of approximately 100mm. Pre-injection with water is recommended for priming and facilitation of reaction.

### Mixing

BluRez CSI50 is supplied in one component packaging ready for application.

### Application

Commence from the widest part of the crack and proceed injecting outwards along the crack in each direction. Turn on pump and slowly increase pressure to a maximum of 30 bar. Stop pumping for every litre injected and allow 1 - 2 minutes for setting. Start and stop injection until the packer will no longer accept material or if the specified pressure has been reached. Move to the next packer and repeat injection process. Continue injection until crack is full and has been adequately sealed. Monitor the effectiveness of the work and allow to settle for 2 - 3 days before returning to site and completing additional injection if required. BluRez CSI50 may be injected into the crack with water at a ratio of 1 : 1.

# BluRez CSI50

## HYDROPHILIC POLYURETHANE INJECTION RESIN

### Product Data

Please refer to Important Notice on following page

Packaging	20kg kit
Ratio	Single component
Viscosity	800cps @ 25°C
Tensile Strength	2.55MPa
Elongation @ Break	400%
Foaming Factor	3 - 3.5*
Start of Foaming	45 seconds*
Gel Time	55 seconds*
End of Foaming	200 seconds*
Tack Free Time	230 seconds*
Shelf Life	12 months

\* Laboratory measurements mixed 1 part water to 3 parts BluRez CSI50 @ 25°C

# BluRez CSI50

## HYDROPHILIC POLYURETHANE INJECTION RESIN

### Contact Bluey

#### HEAD OFFICE QLD

1300 0 BLUEY | [qld@bluey.com.au](mailto:qld@bluey.com.au)

[bluey.com.au](http://bluey.com.au)

#### NSW

[nsw@bluey.com.au](mailto:nsw@bluey.com.au)

#### VIC

[vic@bluey.com.au](mailto:vic@bluey.com.au)

#### SA

[sa@bluey.com.au](mailto:sa@bluey.com.au)

#### WA

[wa@bluey.com.au](mailto:wa@bluey.com.au)

#### TAS

[tas@bluey.com.au](mailto:tas@bluey.com.au)

#### ACT

[act@bluey.com.au](mailto:act@bluey.com.au)

#### NT

[nt@bluey.com.au](mailto:nt@bluey.com.au)

#### NZ

[nz@bluey.com.au](mailto:nz@bluey.com.au)

#### UK/EUROPE

[bluey@bluey.ie](mailto:bluey@bluey.ie)

#### ASIA PACIFIC

[sales\\_sg@quicseal.com](mailto:sales_sg@quicseal.com)

### IMPORTANT NOTICE

This Technical Data Sheet is provided for general information and instruction only. Bluey does not warrant that the information it contains is accurate, reliable or complete. Bluey does not warrant that the product (or any related services) will achieve any of the characteristics set out herein in any particular application in the field, nor that it will be suitable for any specific use or purpose. The properties and characteristics set out herein represent typical testing results under laboratory conditions only. Results of actual product implementation may vary. Site-specific and project-specific criteria will affect product performance, including without limitation: surfaces, materials or products used with the product or to which the product is applied; and weather, climatic or seasonal conditions. The user must take into account all such criteria relevant to the project concerned when considering any desired results, including by undertaking trial mixing and application under site conditions. Not all product parameters are batch tested as part of the manufacturing quality control process, and performance may vary between batches.

If Bluey gives any express written product warranty in relation to the product, that warranty is subject to the foregoing qualifications, despite anything to the contrary in any other document. All other representations, advice, suggestions or promises regarding the product's performance or its implementation, whether verbal or in writing, and whenever given, including in the course of any field services, are expressly disclaimed. Without limiting the foregoing, Bluey will have no liability for loss or damage of any kind if any application specifications are not followed.

The foregoing is not intended to exclude any warranties or guarantees which by law cannot be excluded. Subject only to the foregoing provisions of this Notice, and to the extent permitted by law, Bluey disclaims all liability for loss or damage of any kind suffered as a result of or in connection with the product or its implementation. If such liability cannot be wholly excluded, Bluey's liability will, to the extent permitted by law, be limited to the replacement of the product itself or the direct cost of replacement of the product itself (not including any collateral or consequential loss or damage of any kind).

© Bluey Technologies Pty Ltd